



**Product Code:** B055

### **Ductilometer with Cooling System**

**Standard:** EN 13398, EN 13589 | ASTM D113, D6084 | AASHTO T51

#### **Description:**

Used to determine the bituminous ductility, that is the distance to which a briquette of molten bitumen can be extended under controlled conditions, before breaking. Equipped with an incorporated refrigerating unit for tests with water temperature from + 5° to + 25°C.

### **Technical Specifications**

Test Type: <b>Bituminous ductility determination</b>	Function: <b>Measures extension distance of bitumen briquette before breaking</b>
Temperature Range: <b>+5° to +25°C</b>	Cooling System: <b>Built-in refrigeration for precise temperature control</b>
Temperature Control: <b>Incorporated refrigerating unit</b>	Weight: <b>130 kg</b>
Dimensions: <b>1880x360x680 mm</b>	

No. 15 Chile St. Ph1 Greenheights Subdivision Concepcion 1, Marikina City, Philippines

Tel: (632)8-997-7959 | (632)8-584-5572

Mobile: +63 909 087 9416 | +63 928 395 3532 | +63 918 905 8316

Email: [sales@gemarcph.com](mailto:sales@gemarcph.com) | [technical@gemarcph.com](mailto:technical@gemarcph.com)