



Product Code: S-560

CAPSTONE S-560

Features: Extremely High Strength Gypsum

Description:

S-560 represents the extremely high strength gypsum, which is exclusive in capping gypsum application. Many governments critical of construction in Taiwan requested S-560 as the capping material. Such as the Taiwan High-Speed Rail, highway and bridge construction, etc. The extremely high strength gypsum S-560 is believed to be a trend in the near future.

Technical Specifications

Strength Performance: Over 560 kgf/cm ² (8000 psi)	Water to Gypsum Ratio: 17-18%
Working Time: Ready to use immediately after mixing	Hardening Time: Approximately 30 minutes
Application Type: Extremely high strength capping gypsum	Market Position: Exclusive in capping gypsum application
Industry Trend: Believed to be the future trend in high-strength capping	Final Strength: 560+ kgf/cm ² (equivalent to 8000+ psi)
Critical Applications: Government critical construction projects	Usage Instructions: Simply mix with water at 17-18% ratio and use immediately
Performance Level: Extremely high strength performance	Quality Standards: Meets requirements for critical infrastructure projects

No. 15 Chile St. Ph1 Greenheights Subdivision Concepcion 1, Marikina City, Philippines

Tel: (632)8-997-7959 | (632)8-584-5572

Mobile: +63 909 087 9416 | +63 928 395 3532 | +63 918 905 8316

Email: sales@gemarcph.com | technical@gemarcph.com