



**Product Code:** TS-DRC-007

## Drill Rods & Casing Pipe

### Description:

Comprehensive range of drill rods and casing pipes manufactured to meet 100% of drilling standards using the best quality raw materials. Drill rods are maintained by the chuck of the drill rig and convey rotation, pressure, and drilling water while also handling rapid cooling and slime removal.

### Technical Specifications

<b>Drill Rod Sizes:</b> AW, BW, N, NS-3, H, P, NW, HW, HWT	<b>P Drill Rods:</b> 3000mm length, O.D: 114.3-114.5mm, I.D: 101.6-101.80mm
<b>H Drill Rods:</b> 3000mm length, O.D: 88.90-89.15mm, I.D: 77.8-78.0mm, Pin & Box (heat treatment)	<b>N Drill Rods:</b> 3000mm length, O.D: 69.85-70.05mm, I.D: 60.12-60.33mm
<b>B Drill Rods:</b> 3000mm length, O.D: 55.6-55.8mm, I.D: 46.0-46.2mm	<b>Casing Pipe Sizes:</b> RW, EW, AW, BW, NW, HW, PW (36.5mm to 139.7mm O.D)
<b>Tensile Strength:</b> Min. 900 N/mm <sup>2</sup>	<b>Yield Stress:</b> Min. 800 N/mm <sup>2</sup>
<b>Extension:</b> Min. 14%	<b>Surface Hardness:</b> HRC 30 ~ 35
<b>Roundness:</b> 0.2 Max Standard	<b>Straightness:</b> 0.8/1000mm (Standard)

No. 15 Chile St. Ph1 Greenheights Subdivision Concepcion 1, Marikina City, Philippines

Tel: (632)8-997-7959 | (632)8-584-5572

Mobile: +63 909 087 9416 | +63 928 395 3532 | +63 918 905 8316

Email: sales@gemarcph.com | technical@gemarcph.com