



Product Code: XL 140 DR

MULTIDRILL XL 140 DR

Description:

The FRASTE MULTIDRILL XL140 DR is a versatile and reliable geothermal drilling rig, renowned for its innovation and high quality. Designed for air drilling, its dual rotary head allows simultaneous drilling with drill pipe and casing. User-friendly features include a preventer and cuttings conveyor, ensuring a clean work environment. Like all Fraste rigs, the XL 140 DR prioritizes safety with ergonomic controls and regulatory compliance. Various optional equipment is available.

Technical Specifications

Power: CAT C4.4 - Stage V - Tier 4F - 110 kw (148 Hp) / CAT C4.4 - Stage IIIA - Tier 3 - 106 Kw (142 Hp)	Rotary head stroke: 3700 mm (11,5 ft)
Pull-up: 10000 daN (22480 lbf)	Pull-down: 6800 daN (15287 lbf)
Rotary head for drill pipes - Max torque: 1550 daNm (11432 ft lbf)	Rotary head for drill pipes - Max speed: 160 rpm
Rotary head for drill pipes - Speeds number: 2	Rotary head for casing - Max torque: 2700 daNm (19914 ft lbf)
Rotary head for casing - Max speed: 70 rpm	Rotary head for casing - Speeds number: 2/3
Clamp: Ø 60-355 mm (2,3"-14")	Weight: ~ 9400 Kg (~ 20723 lb)

No. 15 Chile St. Ph1 Greenheights Subdivision Concepcion 1, Marikina City, Philippines

Tel: (632)8-997-7959 | (632)8-584-5572

Mobile: +63 909 087 9416 | +63 928 395 3532 | +63 918 905 8316

Email: sales@gemarcph.com | technical@gemarcph.com